



Z400 Thermal Transfer/Direct Thermal

Printer Specifications

Resolution	203DPI
Print Method	Thermal Transfer/ Direct Thermal
Memory	8 MB RAM/8 MB Flash
Max. Print width	4.09 in./104 mm
Max. Print Speed	Up to 5 ips (127 mm/s)
Media Sensors	Movable Black Mark Sensor/Movable Gap Sensor
Emulation	TSPL, ZPL, EPL, DPL
Interface	USB, USB+Serial, USB+Lan, USB+Serial+Lan(Optional Wireless Connectivity: Bluetooth / Wi-Fi)
Others	Standard SD Card Slot, Optional RTC

Media and Ribbon Characteristics

Media Length	0.39 in.-70 in.(10 mm-1778 mm)
Media Width	1 in.-4.6 in.(25.4 mm-118 mm)
Media Roll Size	5 in./127 mm Outer Diameter/Core Inner Diameter: 1 in.(25.4 mm)
Thickness	0.0023 in.(0.06 mm) Min.; 0.01 in.(0.254 mm) Max.
Media Types	Continuous, Gap, Black mark, Fan-fold, Perforated Media
Ribbon Outside Diameter	2.63 in./67 mm
Max. Ribbon Length	300 Meters (984 ft.)
Ribbon Width	1 in.-4.3 in.(25.4 mm-110 mm)
Ribbon Core I.D.	1 in./25.4 mm

Environment Condition

Operating Temp.	5~40°C (41~104°F)
Storage Temp.	-40~60°C (-40~140°F)
Operating Humidity	25 ~ 85% Non-Condensing
Storage Humidity	10 ~ 90% Non-Condensing

Product Warranty

Printhead life	The earlier of 30 km usage or 1 year
Platen roller life	The earlier of 30 km usage or 1 year
Printer Warranty	1 Year



Admin Office:
Future Image Corporation
#23/2, Reddy Street, West Tambaram,
Chennai - 45



044 - 4202 0848 / +91 950 004 2482 / +91 967 705 6844/ +91 709 201 4441/ +91 709 201 4442



sales@futureimage.in